



**PAPERONE LASER** is engineered for converting needs. **PAPERONE LASER** is available in high-bright white shade and is produced using 100% ECF pulp from PEFC certified renewable plantation fibre. This paper is alkaline sized to meet ISO 9706 for archival quality.

**BENEFITS**



No Post Print Curling



Vibrant Colors



Sharp And Crisp Lines



Lesser Color Bleed

**SPECIFICATIONS**

CHARACTERISTICS	UNITS	TOLERANCE	TEST METHOD	QUALITY SPECIFICATION		
Basis Weight	gsm	±4%	ISO 536	70	75	80
Thickness	µm	±3	ISO 534	97	103	107
Moisture	%	±0.5	ISO 287	4	4	4
CIE Whiteness	#	±2	ISO 11475	158	158	163
ISO Brightness	%	±2	ISO 2470	95	95	95
ISO Opacity	%	±2	ISO 2471	93	94	94
Roughness	ml/min	±50	ISO 8791-2	200	200	200

**END USES**

- Statements
- Plotter Rolls
- Continuous Forms
- Trans-promotional
- Letterheads
- Variable Data Books and Magazines

**PRINTING METHODS**

- Laser

**FINISHINGS**

- Gluing
- Spiral Binding
- Limp Binding
- Saddle Stitch
- Perfect Binding
- Cutting and Folding



Specifications are accurate as of Oct 2015 in accordance with international standards for tolerances and are subjected to changes.

