

Product Information and Specifications PaperOne™ Laser

PAPERONE™ LASER is engineered for converting needs. **PAPERONE LASER™** is available in high-bright white shade and is produced using 100% ECF pulp from PEFC certified renewable plantation fibre. This paper is alkaline sized to meet ISO 9706 for archival quality.

APPLICATIONS

- Statements
- Plotter Rolls
- Continuous Forms
- Trans-promotional
- Letterheads
- Variable Data Books and Magazines

FINISHINGS

- Gluing
- Spiral Binding
- Limp Binding
- Saddle Stitch
- Perfect Binding
- Cutting and Folding

PRINTING METHODS

- Laser

BENEFITS



No Post
Print Curling



Vibrant
Colors



Sharp And
Crisp Lines



Lesser Color
Bleed



SPECIFICATIONS

CHARACTERISTICS	UNITS	TOLERANCE	TEST METHOD	QUALITY SPECIFICATION		
Basis Weight	gsm	± 4%	ISO 536	70	75	80
Thickness	µm	± 3	ISO 534	96	102	106
Moisture	%	± 0.5	ISO 287	4	4	4
CIE Whiteness	#	± 2	ISO 11475	158	158	158
ISO Brightness	%	± 2	ISO 2470	95	95	95
ISO Opacity	%	± 2	ISO 2471	93	94	94
Roughness	ml/min	± 50	ISO 8791-2	210	210	210



Specifications are accurate as of Oct 2015 in accordance with international standards for tolerances and subjected to changes.
*Based on benchmarking studies under controlled conditions, subject to change.